



Science Arts & Métiers (SAM)

is an open access repository that collects the work of Arts et Métiers Institute of Technology researchers and makes it freely available over the web where possible.

This is an author-deposited version published in: <https://sam.ensam.eu>
Handle ID: <http://hdl.handle.net/10985/11396>

To cite this version :

Patrick BOT, Marc RABAUD, Goulven THOMAS, Alessandro LOMBARDI, Charles LEBRET -
Sharp Transition in the Lift Force of a Fluid Flowing Past Nonsymmetrical Obstacles: Evidence for
a Lift Crisis in the Drag Crisis Regime - Physical Review Letters - Vol. 117, p.234501-1 à 5 - 2016

Any correspondence concerning this service should be sent to the repository

Administrator : scienceouverte@ensam.eu



Supplemental material to “Lift crisis on non-symmetrical obstacles”

This supplemental material shows the results briefly given in the paper for three different sections.




Figure SM1: The three sections tested (bodies 2, 1 and 3 from left to right).

As shown in Figures SM2 and SM3, the same behavior is evidenced on the 3 tested sections showing a simultaneous lift and drag crisis.




Figure SM2: Lift and drag crisis on the three sections tested. The crisis is less abrupt for the circular-back profile than for the other sections.




Figure SM3: Time-averaged velocity field below (top line) and above (bottom line) the critical Reynolds number, for the circular-back section (left column) and the half-cylinder section (right column).

The following table summarizes the results obtained on the three sections.

Profile	1 Circular arc	2 Circular-back	3 Half-cylinder
$Re_c (10^5)$	2.0	2.5	3.0
C_{L0}	0.08	0.24	-0.103
C_L below	-0.6	-0.3	-0.6
C_L above	0.87	0.9	0.53
C_D below	0.2	0.18	0.57
C_D above	0.1	0.04	0.25
γ	0.2	0.5	0.2
C_L/C_D below	-3	-0.2	-0.1
C_L/C_D above (max)	8.5	22	2
C_x below	0.9	0.81	1.14
C_x above	0.45	0.18	0.5

Table SM1: Comparison between the 3 profiles. C_L and C_D are defined with the chord length c as the reference length C_x is defined with the section thickness as the reference length. Values below and above the transition are given far away from the threshold Re_c .

Comparing the circular-back section with the circular arc section:

- The critical Reynolds number Re_c is slightly higher: $2.5 \cdot 10^5$ instead of $2.0 \cdot 10^5$,
- The lift coefficient above Re_c is similar and the drag coefficient is about half;
- The lift coefficient below Re_c is about half and the drag coefficient is similar.

Comparing the half-cylinder section with the circular arc section:

- The critical Reynolds number Re_c is higher: $3.0 \cdot 10^5$ instead of $2.0 \cdot 10^5$,
- The lift coefficient above Re_c is lower;
- The lift coefficient below Re_c is similar;
- The drag coefficient C_D (defined with the chord length) is far higher for all Re ; the drag coefficient C_x defined with the frontal area is similar (of order 1 below Re_c , of order 0.5 above Re_c).




Figure SM4: Separation point location x/c for the 3 profiles.




Figure SM5: Lift-to-drag ratio for the three different profiles. The circular-back profile has a large lift-to-drag ratio at high Reynolds numbers.