



Science Arts & Métiers (SAM)

is an open access repository that collects the work of Arts et Métiers Institute of Technology researchers and makes it freely available over the web where possible.

This is an author-deposited version published in: <https://sam.ensam.eu>
Handle ID: <http://hdl.handle.net/10985/8635>

To cite this version :

Nadim EL HAYEK, Mohamed DAMAK, Hichem NOUIRA, Nabil ANWER, Eric NYIRI, Olivier GIBARU - Fast B-Spline 2D Curve Fitting for unorganized Noisy Datasets - 2014

Any correspondence concerning this service should be sent to the repository

Administrator : scienceouverte@ensam.eu



Fast B-Spline 2D Curve Fitting for unorganized Noisy Datasets

Authors: N El-Hayek^{1,2}, O Gibaru¹, M Damak^{1,3}, H Nouria², N Anwer⁴ and E. Nyiri¹

- 1- Arts et Métiers ParisTech, Laboratory of Information Sciences and Systems (LSIS), 8 Blvd Louis XIV, 59046 Lille, France
 2- Laboratoire Commun de Métrologie (LCM), 1 r. Gaston Boissier, 75015 Paris, France
 3- GEOMNIA, 3D Metrology Engineering and Software Solutions, 165 Avenue de Bretagne, EuraTechnologies 59000 Lille, France
 4- Ecole Normale Supérieure de Cachan, University Research Laboratory in Automated Production, 61 av. Président Wilson, 94235 Cachan, France

Context

- Optical and Tactile Metrology for Absolute Form Characterization (EURAMET project IND10)
- Fast polynomial spline curve reconstruction from very large unstructured datasets

Objective

Curve reconstruction of freeform shapes, specifically turbine blades, from data with unknown topology


Objective function

$$\min_{t_1, t_2, \dots, t_m} \sum_j \left((MT_m)_j - \delta_j \right)^2$$

M is the subdivision matrix (1)

$T = \{t_1, t_2, \dots, t_m\}$ is the control points translations vector

Discrete B-Spline Convection scheme



✓ NO initial parameterization

✓ NO differential calculations

✓ NO sampling requirements

✓ Invariance of final control polygon geometry to initial position and orientation

Methodology


Coincide new B-Spline curve at iteration (i+1) with data points by minimizing the distances

The B-Spline (green) is initialized by a few control points around the data.

Distances δ_i are calculated with geometrical and topological considerations.

L_2 minimization \rightarrow translation vectors $\{t_1, t_2, \dots, t_m\}$ by which control points must move.

If the minimization does not meet the error tolerance, point insertion is applied locally.



(1) Subdivision relation

$$q_j^{(i)} = MC_m^{(i)}$$

(2) Convection equation

$$C_m^{(i+1)} = C_m^{(i)} + T_m^{(i)}$$

(3) Solution equation

$$q_j^{(i+1)} = M(C_m^{(i)} + T_m^{(i)})$$

(i): iteration i

p: Point set

q: Piecewise linear B-Spline curve

c: Control points

delta: Distances


epsilon: Distance vectors

t: translation vectors


Experimental results

Invariance to point-set orientation


ϵ = mean of residual errors




8 final control points:
 $\epsilon \approx 0.0015$ mm, 140 iterations




8 final control points:
 $\epsilon \approx 0.00088$ mm, 140 iterations




8 final control points:
 $\epsilon \approx 0.0023$ mm, 140 iterations



10 final control points:
 $\epsilon \approx 0.0024$ mm, 140 iterations



10 final control points:
 $\epsilon \approx 0.0017$ mm, 140 iterations



11 final control points:
 $\epsilon \approx 0.00091$ mm, 140 iterations

Conclusions

- The B-Spline convection algorithm is founded on discrete computations.
- The algorithm is robust regarding the relative initial position of both the B-Spline and the data.
- The algorithm is tested on several shapes and returns residual errors below threshold if not too small.
- The initial number of control points must be minimal.
- The algorithm can be subject to time complexity improvement.
- Precision is not yet controllably achievable.

- [1] Speer T., M. Kuppe, and J. Hoschek. Global reparameterization for curve approximation, in Computer Aided Geometric Design, 1998.
 [2] Wang W., H. Pottmann, and Y. Liu. Fitting B-Spline Curves to Point Clouds by Curvature-Based Squared Distance Minimization, in ACM Transactions on Graphics, 2006.
 [3] Zheng W., P. Bo, Y. Liu, and W. Wang. Fast B-spline curve fitting by L-BFGS, in Computer Aided Geometric Design, 2012.

Acknowledgement:

The authors sincerely thank the EMRP organization. The EMRP is jointly funded by the EMRP participating countries within EURAMET and the European Union