



### **Science Arts & Métiers (SAM)**

is an open access repository that collects the work of Arts et Métiers Institute of Technology researchers and makes it freely available over the web where possible.

This is an author-deposited version published in: <https://sam.ensam.eu>  
Handle ID: <http://hdl.handle.net/10985/9984>

#### **To cite this version :**

Azita AHMADI-SENICHAULT, Gérard VIGNOLES, Olivia COINDREAU, William ROS, Fagner GOULARD DIAS - Effective heat conductivities of partly infiltrated fibrous media - 2009

Any correspondence concerning this service should be sent to the repository

Administrator : [scienceouverte@ensam.eu](mailto:scienceouverte@ensam.eu)



# Effective heat conductivities of partly infiltrated fibrous media

Azita AHMADI<sup>1</sup>, Gérard VIGNOLES<sup>2</sup>, Olivia COINDREAU<sup>2</sup>,  
William ROS<sup>2</sup> and Fagner GOULART DIAS<sup>1</sup>

<sup>1</sup> *TREFLE Laboratory (UMR CNRS 8508), Arts et Métiers ParsiTech, Bordeaux 1  
University, Esplanade des Arts et Métiers, 33405 Talence, France*

<sup>2</sup> *Bordeaux 1 University, Laboratoire des Composites ThermoStructuraux (LCTS), 3 Allée La  
Boétie, 33600 Pessac, France*

The present work has been motivated by the context of feeding a global model of thermal-gradient chemical vapour infiltration process for the fabrication of fibre-reinforced ceramic matrix composites: the heat conductivity has to be known in the material as a function of the pore volume distribution, at different stages of infiltration. Since the composite preform is made of woven fibres, the medium is highly anisotropic: the heat conductivity has a tensorial character which has to be retrieved.

We propose an approach based on a double up-scaling. First, the fibre-scale effective longitudinal and transverse conductivities are computed for several volume fractions of matrix and fibres, using a periodic unit cell as a computational domain. The second change of scale takes precisely into account the actual architecture of the composite thanks to 3D X-ray tomographic imaging. The 3D blocks are processed in order to retrieve the local orientation of the fibres in various sub-domains; the local heat conductivities are then affected to the sub-domains, and a volume averaging procedure is applied for the determination of the global effective conductivity.

Several application examples are presented and discussed.