



Science Arts & Métiers (SAM)

is an open access repository that collects the work of Arts et Métiers Institute of Technology researchers and makes it freely available over the web where possible.

This is an author-deposited version published in: <https://sam.ensam.eu>
Handle ID: <http://hdl.handle.net/10985/17060>

To cite this version :

Pierre-Yves ROHAN, H el ene PILLET, Wafa SKALLI, Julien TRNKA, Mathieu MANASSERO, V eronique VIATEAU, Julien CAROUX, Laurent CORT E - Functional evaluation of anterior cruciate ligament autografts in pre-clinical animal models - 2017

Any correspondence concerning this service should be sent to the repository

Administrator : archiveouverte@ensam.eu



Functional evaluation of anterior cruciate ligament autografts in pre-clinical animal models

Pierre-Yves ROHAN (1), H el ene PILLET (1), Wafa SKALLI (1), Julien TRNKA (2),
Mathieu MANASSERO (2), V eronique VIATEAU (2), Julien CAROUX (3,4), Laurent CORTE (3,4)

1 Institut de Biom ecanique Humaine Georges Charpark, Arts et Metiers ParisTech, 151 bd de l'H opital, 75013. Paris, France

2 Ecole Nationale V et rinaire d'Alfort, Service de Chirurgie, 7 av du G en eral de Gaulle, 94700 Maison-Alfort, France

3 Centre des Mat eriaux – CNRS : UMR7633, MINES ParisTech, PSL Research University, France

4 Mati ere Molle et Chimie – CNRS : UMR 7167, ESPCI Paris, PSL Research University, France

Introduction

Rupture of the Anterior Cruciate Ligament (ACL) affects about 1 person over 3000 every year. The current standard care is based on ligament reconstruction by autograft from tendon tissues and is considered as the gold standard. Yet, autograft reconstruction presents serious limitations. Recent developments in artificial ligaments are promising and could potentially address the currently growing demand from surgeons and patients for an off-the-shelf alternate solution. However, before these can be commonly used in clinical routine, their biocompatibility and biomechanical performance for the short and long terms must be studied in pre-clinical animal models. Building upon the work of [1], we propose in this contribution a methodology for assessing the biomechanical performance of artificial ligaments, and to provide reference data (autografts) using an animal model (sheep) at 3 months after implantation.

Materials and Methods

Surgery and specimen preparation

14 fresh frozen lower limbs were used in this study, seven left (autograft implantation) and seven right (contralateral) knees. These were harvested from seven sheep sacrificed 3 months after implantation. The biomechanical analysis of the knees consisted of four successive in vitro experiments: three kinematics tests (flexion-extension, varus-valgus laxity and anterior drawer tests) and a pull-out destructive test.

Kinematics analysis: flexion-extension and laxity tests

The kinematic analysis was performed using specific motorized devices adapted from previously described and validated ones [1]. The protocol combined motion analysis of tripods screwed in the bony structures and 3D personalized reconstruction (figure 1) from low-dose X-ray system (EOS, EOS Imaging, Paris, France) [1,2,3,4].




Figure 1: Anatomical frames defined for each bone (a) Profile (b) Frontal and (c) oblique views respectively.

Pull-out destructive tests

The pull-out tests were performed using an INSTRON 5566 testing machine (Instron Ltd., Buckinghamshire, England) instrumented with a 5 kN load cell. After conditioning, a tension load was applied to the specimen (5 mm/min) until total failure.

Data analysis: mobility assessment and statistical tests

The following parameters were extracted to allow the comparison with the literature [1] (i) Internal rotation Ry ($^{\circ}$) value for a 40 $^{\circ}$ flexion angle (Ry_40), (ii) Anterior Tibial Translation (mm) for 100 N loading (ATT_100), (iii) Varus Valgus amplitude ($^{\circ}$) at 4 Nm loading (VV_4) and (iv) the Failure load (N) (FL).

Results and discussion

Table 1 below summarizes the results :

mean \pm SD.	Current study		Guerard et al. [1]	
	Contralateral knees	Autograft (3 months)	Contralateral knees	LARS (3 months)
Ry_40	-14.9 \pm 2.1 (n=7)	-10.8 \pm 4.0 (n=7)	-14.5 \pm 3.1 (n=4)	-9.8 \pm 2.6 (n=4)
ATT_100	0.9 \pm 0.2 (n=7)	2.8 \pm 0.9 (n=7)	0.6 \pm 0.5 (n=5)	2.8 \pm 1.7 (n=6)
VV_4	9.9 \pm 4.6 (n=7)	15.2 \pm 2.2 (n=7)	12.0 \pm 3.8 (n=4)	12.9 \pm 2.2 (n=6)
FL	912 \pm 145 (n=7)	183 \pm 80 (n=7)	1214 \pm 286 (n=6)	144 \pm 69 (n=5)

Table 1: Kinematic results and failure loads

The results shows a good consistency for kinematic parameters of the contralateral knees. The failure load was clearly different due to the interindividual variability. As concerns the autograft, a reduction of internal rotation during the flexion motion and an increase of the laxity in ATT could be observed. The failure load was also decreased for the grafted knee.

References

- Gu erard et al, Adv. Biomech. Appl., 1:239–52, 2014.
- Azmy et al, Orthop. Traumatol. Surg. Res., 96:28–36, 2010
- Chaibi et al, Comput. Methods Biomech. Biomed. Engin. 15:457–66, 2012
- Quijano et al, Med. Eng. Phys. 35:1703–12, 2013.

Acknowledgements

This work was supported by the French National Research Agency (ANR project n o ANR-08-ETEC-003)