



Science Arts & Métiers (SAM)

is an open access repository that collects the work of Arts et Métiers Institute of Technology researchers and makes it freely available over the web where possible.

This is an author-deposited version published in: <https://sam.ensam.eu>
Handle ID: [.http://hdl.handle.net/10985/20336](http://hdl.handle.net/10985/20336)

To cite this version :

Fessal KPEKY, Farid ABED-MERAIM, El Mostafa DAYA - Influence of variability in geometric and material parameters on the damping properties of multilayer structures - 2016

Any correspondence concerning this service should be sent to the repository

Administrator : archiveouverte@ensam.eu



Influence of variability in geometric and material parameters on the damping properties of multilayer structures

Fessal KPEKY^{1,3}, Farid ABED-MERAIM^{2,3*} and El-Mostafa DAYA^{1,3}

¹ LEM3, UMR CNRS 7239, Université de Lorraine, Ile du Saulcy Metz Cedex 01, France

² LEM3, UMR CNRS 7239, Arts et Métiers ParisTech, 4 rue A. Fresnel, 57078 Metz Cedex 03, France

³ Laboratory of Excellence on Design of Alloy Metals for low-mAss Structures (DAMAS), France

Abstract. In this work, we present finite element models based on the solid–shell approach, which have been specifically designed for the modeling of multilayer structures. The originality in the current study lies in the analysis of variability in the design parameters, which could be of geometric or material type. The first type of imperfections generally results from the manufacturing of such structures [1], while the second source of variability arises from the mechanical parameters of the same material, as identified in the literature (e.g., Aluminum Young modulus equal to 70.3 GPa in [2], while estimated as 69 GPa in [3]). Therefore, it is of importance to assess the influence of these uncertainties on the design of actual structures. To this end, several studies have been proposed in the literature, among which in reference [4], the MSP (Modal Stability Procedure) was combined with the MCS (Monte Carlo Simulation). The approach we propose is rather simple and is based on the uncertainty on the actual values of several parameters in some well-defined intervals. The developed method is applied to modeling the vibrations of multilayer shell structures made of elastic layers, viscoelastic and piezoelectric materials. The resulting problem is discretized by linear and quadratic solid–shell finite elements developed in [5, 6] and extended to viscoelastic sandwich structures in [7]. To solve the associated nonlinear equations, we adopt the method that couples the homotopy to ANM (Asymptotic Numerical Method) and AD (Automatic Differentiation) proposed in [8]. The obtained results provide information on the tolerance margin of error that can be committed without compromising structural integrity.

Keywords: Variability, Solid–shell finite elements, Multilayer structures, Vibrations, Viscoelasticity, Piezoelectricity, Asymptotic numerical method.

References

- [1] Jung B, Lee D, Youn B, Lee S. A statistical characterization method for damping material properties and its application to structural-acoustic system design. *Journal of Mechanical Science and Technology*. 2011;25:1893-904.
- [2] Trinidad MA. Contrôle hybride actif-passif des vibrations de structures par des matériaux piézoélectriques et viscoélastiques: poutres sandwich/multicouches intelligentes [Thèse de doctorat]: Conservatoire National des Arts et Métiers, 2001.
- [3] Bilasse M. Modélisation numérique des vibrations linéaires et non linéaires des structures sandwichs à âme viscoélastique [Thèse de doctorat]: Université Paul Verlaine, Metz, 2010.
- [4] Hamdaoui M, Druesne F, Daya EM. Variability analysis of frequency dependent visco-elastic three-layered beams. *Composite Structures*. 2015;131:238-47.
- [5] Abed-Meraim F, Combescure A. An improved assumed strain solid–shell element formulation with physical stabilization for geometric non-linear applications and elastic-plastic stability analysis. *International Journal for Numerical Methods in Engineering*. 2009;80:1640-86.
- [6] Abed-Meraim F, Trinh VD, Combescure A. New quadratic solid–shell elements and their evaluation on linear benchmark problems. *Computing*. 2013;95:373-94.
- [7] Kpeky F, Boudaoud H, Abed-Meraim F, Daya EM. Modeling of viscoelastic sandwich beams using solid–shell finite elements. *Composite Structures*. 2015;133:105-16.
- [8] Bilasse M, Charpentier I, Daya EM, Koutsawa Y. A generic approach for the solution of nonlinear residual equations. Part II: Homotopy and complex nonlinear eigenvalue method. *Computer Methods in Applied Mechanics and Engineering*. 2009;198:3999-4004.