

## Science Arts & Métiers (SAM)

is an open access repository that collects the work of Arts et Métiers Institute of Technology researchers and makes it freely available over the web where possible.

This is an author-deposited version published in: https://sam.ensam.eu Handle ID: .http://hdl.handle.net/10985/9984

To cite this version :

Gérard VIGNOLES, Olivia COINDREAU, William ROS, Fagner COULARD DIAS, Azita AHMADI-SENICHAULT - Effective heat conductivities of partly infiltrated fibrous media - 2009

Any correspondence concerning this service should be sent to the repository Administrator : scienceouverte@ensam.eu



## Effective heat conductivities of partly infiltrated fibrous media

Azita AHMADI<sup>1</sup>, Gérard VIGNOLES<sup>2</sup>, Olivia COINDREAU<sup>2</sup>, William ROS<sup>2</sup> and Fagner GOULART DIAS<sup>1</sup>

 <sup>1</sup> TREFLE Laboratory (UMR CNRS 8508), Arts et Métiers ParsiTech, Bordeaux 1 University, Esplanade des Arts et Métiers, 33405 Talence, France
<sup>2</sup> Bordeaux 1 University, Laboratoire des Composites ThermoStructuraux (LCTS), 3 Allée La Boëtie, 33600 Pessac, France

The present work has been motivated by the context of feeding a global model of thermalgradient chemical vapour infiltration process for the fabrication of fibre-reinforced ceramic matrix composites: the heat conductivity has to be known in the material as a function of the pore volume distribution, at different stages of infiltration. Since the composite preform is made of woven fibres, the medium is highly anisotropic: the heat conductivity has a tensorial character which has to be retrieved.

We propose an approach based on a double up-scaling. First, the fibre-scale effective longitudinal and transverse conductivities are computed for several volume fractions of matrix and fibres, using a periodic unit cell as a computational domain. The second change of scale takes precisely into account the actual architecture of the composite thanks to 3D X-ray tomographic imaging. The 3D blocks are processed in order to retrieve the local orientation of the fibres in various sub-domains; the local heat conductivities are then affected to the sub-domains, and a volume averaging procedure is applied for the determination of the global effective conductivity.

Several application examples are presented and discussed.